A١

10

Patent Claims

- 1. An electrode arrangement for an electrical component and carrier for sensors, which arrangement is applied on a arrangement consisting of two (1),this which are electrically conductive electrodes (2), electrically connected with one another, and a surface structure with suitable dimensions for the representation of the conductivities of the electrode arrangement and/or the substance of a sensor-active layer by of conductance of a measuring probe or of a function element, so characterized that on a dielectric substrate (1) between two electrodes (2) a number of conductive islands (3), which are not or are not essentially connected with one another, are applied as a two-dimensional area arrangement.
- 2. An electrode arrangement for an electrical component and carrier for sensors, which arrangement is applied on a consisting this arrangement substrate (1), electrically conductive electrodes (2), which are not electrically connected with one another, and a surface structure with suitable dimensions for the representation 20 of the conductivities of the electrode arrangement and/or layer by sensor-active substance of a the conductance of a measuring probe or of a function element according to claim 1, so characterized that the structure (3) consists of islands conductive 25 distribution of conductive substances on any insulating substrate (1).
- 3. An electrode arrangement for an electrical component and carrier for sensors, which arrangement is applied on a substrate (1), this arrangement consisting of two electrically conductive electrodes (2), which are not electrically connected with one another, and a surface

12



...: <u>-</u>_

15

20

25

U

structure with suitable dimensions for the representation of the conductivities of the electrode arrangement and/or layer by the substance of a sensor-active conductance of a measuring probe or of a function element so characterized that the according to claim 1, substance of the conductive islands (3) is firmly set on the substrate (1) and in particular it is sputtered on, steamed on, squirted on, dabbed on, imprinted or sprayed on.

4 An electrode arrangement for an electrical component and carrier for sensors, which arrangement is applied on a this arrangement consisting of two substrate (1), electrically conductive electrodes (2), which are not electrically connected with one another, and a surface structure with suitable dimensions for the representation of the conductivities of the electrode arrangement and/or the \substance of a sensor-active layer conductance of a measuring probe or of a function element so characterized that the according to claim 1, (3) are arranged within special conductive **\s**lands geometric figures.

5. An electrode arrangement for an electrical component and carrier for sensors, which arrangement is applied on a this arrangement consisting substrate (1), electrically conductive electrodes (2), which are not electrically connected with one another, and a surface structure with suitable dimensions for the representation of the conductivities of the electrode arrangement and/or layer a sensor-active the substance of conductance of a measuring probe or of a function element so characterized that the according to claim 1, surface of the carrier for a sensor is coated with a material-selective substance.

20

25

Cont

- 6. An electrode arrangement for an electrical component and carrier for sensors, which arrangement is applied on a this arrangement consisting (1), electrically conductive electrodes (2), which are electrically connected with one another, and a surface structure with suitable dimensions for the representation of the conductivities of the electrode arrangement and/or by of the substance of a sensor-active layer conductance of a measuring probe or of a function element so characterized that a carrier according to claim 1, for the sensor with a sufficiently thin substrate (1) has a sensor-active layer on all sides.
- 7. An electrode arrangement for an electrical component and carrier for sensors, which arrangement is applied on a this arrangement consisting substrate (1), which are electrically conductive electrodes (2), electrically connected with one another, and a surface structure with suitable dimensions for the representation of the conductivities of the electrode arrangement and/or sensor-active layer of the substance of a conductance of a measuring probe or of a function element so characterized that the according to claim 1, conductive islands (3) in their short-range order show hyperstructures with anisometries of the substances with respect to the substrate.
 - 8. An electrode arrangement for an electrical component and carrier for sensors, which arrangement is applied on a substrate (1), this arrangement consisting of two electrically conductive electrodes (2), which are not electrically connected with one another, and a surface structure with suitable dimensions for the representation of the conductivities of the electrode arrangement and/or



of the substance of a sensor-active layer by the conductance of a measuring probe or of a function element according to claim 1, so characterized that isotropic structures of conductive islands (3) with ring-shaped electrodes (2) are arranged on the substrate (1).

9. An electrode arrangement for an electrical component and carrier for sensors, which arrangement is applied on a this arrangement consisting substrate (1), electrically conductive electrodes (2), which are not electrically connected with one another, and a surface structure with suitable dimensions for the representation of the conductivities of the electrode arrangement and/or layer substance of a sensor-active the conductance of a measuring probe or of a function element so characterized that the according to claim 1, electrode arrangement is designed as a large area as a function element in particular as panel heating elements or photo cells.

A PAGE OF DRAWINGS ON THIS